

Thinner No.9

Thinners & Solvents

Polyurethane Thinner



PRODUCT DESCRIPTION

Thinner No.9 is suitable for thinning and/or equipment cleaning in association with: Perfection Plus, Perfection, Perfection Undercoat.

PRODUCT INFORMATION

Colour	YTA006
Specific Gravity	1.025
Volume Solids	0%
Typical Shelf Life	2 yrs
VOC (As Supplied)	1025 g/l
Unit Size	1 Lt

DRYING/OVERCOATING INFORMATION

Drying

Overcoating

Substrate Temperature

Overcoated By	5°C (41°F)		10°C (50°F)		23°C (73°F)		35°C (95°F)	
	Min	Max	Min	Max	Min	Max	Min	Max

APPLICATION AND USE

Method	When using for surface wipe down, turn the cloth frequently to avoid re-applying residues.
Hints	Ventilation and Humidity Control Ensure adequate ventilation during use.
Some Important Points	No special restrictions.
Compatibility/Substrates	Suitable for use with polyurethane paints and varnishes.

TRANSPORTATION, STORAGE AND SAFETY INFORMATION

Storage	GENERAL INFORMATION: Exposure to air and extremes of temperature should be avoided. For the full shelf life of this product to be realised ensure that between use the container is firmly closed and the temperature is between 5°C/41°F and 35°C/95°F. Keep out of direct sunlight. TRANSPORTATION: The product should be kept in securely closed containers during transport and storage.
Safety	GENERAL: Read the label safety section for Health and Safety Information, also available from our Technical Help Line. DISPOSAL: Do not discard tins or pour paint into water courses, use the facilities provided. It is best to allow paints to harden before disposal. Remainders of Thinner No.9 cannot be disposed of through the municipal waste route or dumped without permit. Disposal of remainders must be arranged for in consultation with the authorities.

IMPORTANT NOTES

The information given in this sheet is not intended to be exhaustive. Any person using the product without first making further written enquiries as to the suitability of the product for the intended purpose does so at their own risk and we can accept no responsibility for the performance of the product or for any loss or damage (other than death or personal injury resulting from negligence) arising out of such use. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.

Please refer to your local representative or visit www.yachtpaint.com for further information.

All trademarks mentioned in this publication are owned by, or licensed to, the AkzoNobel group of companies. © AkzoNobel 2015.